

# BatteryShip.com

## Palm Tungsten E2 Battery Installation Instructions

**PLEASE NOTE:** Patience and care, along with some technical and hand tool ability, are required for the successful replacement of a Palm Tungsten E2 battery. Read all instructions and back up your data **BEFORE** beginning. **Excessive force may result in damage to your PDA.** The instructions below come with no warranty or guarantee. By utilizing these instructions, you agree to hold Batteryship.com blameless and unaccountable for any and all damages, problems, or personal injuries that may or may not arise by your use of these instructions. Replacing your Tungsten E2 battery may void any warranty on your device.

Make sure your PDA is off.

1. Remove the four screws in the back of the case and set them aside. Our tool kit includes 2 Torx screwdrivers. The smaller T5 Torx screwdriver should be used to remove standard screws. If it is not the correct size for the screws in your device, please let us know. If the screws seem larger than the T5 screwdriver, try the T6 Torx instead.
2. Open the back case very carefully and not completely, keeping in mind that the battery will probably stick to the back case while it is connected to the motherboard, so the case will not be able to open completely until the battery has been disconnected from the motherboard. You can use the larger metal flathead screwdriver in our tool kit or the green plastic pry tool to help pry open the case if needed.
3. When you have opened the case enough to access the connector, unplug the battery connector for the original battery from the motherboard.
4. Open the back case completely and remove the original battery (carefully prying it out if needed), making sure to notice how the battery was oriented. Be very careful not to puncture or damage the battery when you remove it.
5. Plug the new battery's connector into the motherboard.
6. Place the new battery (oriented correctly) into the battery compartment.
7. Replace the back cover and re-install the four screws.
8. Charge the new battery for at least 3-4 hours.
9. Dispose of the original battery correctly.

**PLEASE NOTE:** Our tools fit the majority of Palms, but some devices may have different screws installed for various reasons. If our tools do not fit your device, you may have the appropriate tool in a tool kit you already own. You can also check your local hardware or electronics store if you do not have the right tool at home.